



TOLERANCES TANK CAPACITY -0% / +10 OVERALL LENGTH -0" / +2" OVERALL WIDTH -0" / +1" OVERALL HEIGHT -1/2" / +1/2" OTHER DIMENSIONS -1/4" / +1/4"		UL 142 (BUILT & LABELED) HOLDDOWNS ARE SEISMIC RATED DOUBLE WALL TANK SADDLE TANK		STEEL: ASTM A36 PRIMARY TANK SHELL: 10 GAUGE (9/64") HEAD: 10 GAUGE (9/64")		COATING: "R" EXTERIOR COATING, ACE 1A RED SHOP COAT 1-3 MILS "A" EXTERIOR ACE 3A COATING: SP-6 GRIT BLAST 3A COLOR: #WH01 (WHITE) 1 CT TN-161 EPOXY 3.0-5.0 MILS 1 CT TN-74 URETHANE 2.0-3.0 MILS TDFT 5.0-8.0 MILS		SPECIAL INSTRUCTIONS PLUG TIGHT WRENCH PLUG TIGHT WITH PIPE DOPE ON THREADS AND TESTED LEAK FREE.		APPROXIMATE SHIPPING WEIGHT 2,050 LBS. TANK VENT CAPACITY 147,000 PRIMARY TANK 147,000 SECONDARY TANK		DRW BY - REV No 1 SHEET 2 OF -
1-206-281-5000 Acetank & Equipment COPYRIGHT 1997 ACE TANK & EQUIPMENT		AceSaddleLite II - 1,100 GALLON ACE PART No. AC01100U2S4 QTY: 1 (F:1111ACSHOPISADDLEU2S4I011002-ORTHR.GCD-1.32)		SECONDARY TANK SHELL: 12 GAUGE (7/64") HEAD: 10 GAUGE (9/64")		INTERIOR: BARE STEEL		- - -		04-01-02 SUPERCEDES 01-01-02		